

NuGrout™

Grout Colorant and Sealer



TECHNICAL DATA SHEET

DESCRIPTION

NuGrout is a powerful, 100% acrylic colorant and sealer that penetrates deep into grout to add a fresh, new appearance that will renew the look of any tile installation.

NuGrout comes in 24 of the most stylish colors and, when dry, permanently seals the grout to help protect its new brilliance against mold, mildew and stains*.

RECOMMENDED USES

- Use to change the color of grout joints to alter or enhance the look of an installation
- Use to refresh grout joints to resemble their original appearance
- Use for interior and exterior grout coloring applications
- Use to seal grout joints so they resist stains, dirt and grime
- NuGrout is not recommended for submerged applications, such as pools or fountains.

APPLICATION INSTRUCTIONS

STEP 1: Prepare Grout Surface

Thoroughly clean and lightly etch all grout surfaces to be coated using

NuGrout – Grout Cleaner and Pre-treat, removing all dust, dirt, soap-scum, contaminants and other deleterious materials (see Technical Data Sheet for details).

STEP 2: Application

- If using more than 1 bottle of a single color for an application, mix all material together in a larger container prior to use to ensure color is consistent.
- Sealing of porous tile may be required prior to application of grout colorant to ensure it is not absorbed into the tile.
- Spread colorant evenly onto grout surface using a good quality brush or roller working it deeply into the surface using a back-and-forth motion. For best results, apply in two coats (waiting 2-4 hours drying time between coats).

STEP 3: Clean Up

NuGrout cleans up easily with warm, soapy water and a sponge or rag.

Drying Time

NuGrout dries tack-free after 30 minutes and is ready for a second coat after 2-4 hours (depending upon climate conditions). NuGrout is ready for light foot traffic after only 2-4 hours, normal foot traffic after 24 hours, and heavy, commercial traffic after only 72 hours. Allow up to 72 hours drying time for areas subjected to high humidity.

TECHNICAL INFORMATION

Drying time.....	Dries tack-free in 30 min.; recoat after 2-4 hours; final cure after 24 hours for normal traffic; 72 hours for heavy traffic
Thinning.....	Generally not required
Flash point.....	Over 214° F
Clean up.....	Warm, soapy water
Sheen.....	Flat 10 at 60°

Packaging

8 fl. oz., 1/2 pint (237 ml) bottle

* When properly applied, NuGrout with Microbe-Blocker inhibits the growth of surface mold and mildew. Proper maintenance and cleaning is still necessary because microbes can grow on other surface substances, such as soap scum, dirt and grime.

APPROXIMATE COVERAGES

The coverage information provided is approximate and given for estimating purposes only.

Tile Size	Grout Joint Width		
	1/8" (3 mm)	3/16" (4.5 mm)	1/4" (6 mm)
1" x 1" (25 x 25 mm)	—	50 sq ft (4.7 m ²)	—
3" x 3" (75 x 75 mm)	—	85 sq ft (7.9 m ²)	—
4" x 4" (10 x 10 cm)	200 sq ft (18.6 m ²)	95 sq ft (8.8 m ²)	80 sq ft (7.4 m ²)
6" x 6" (15 x 15 cm)	225 sq ft (20.9 m ²)	110 sq ft (10.2 m ²)	95 sq ft (8.8 m ²)
8" x 8" (25 x 25 cm)	250 sq ft (23.2 m ²)	125 sq ft (11.6 m ²)	110 sq ft (10.2 m ²)
12" x 12" (33 x 33 cm)	300 sq ft (27.9 m ²)	145 sq ft (13.4 m ²)	125 sq ft (11.6 m ²)
16" x 16" (41 x 41 cm)	360 sq ft (10.2 m ²)	175 sq ft (16.3 m ²)	135 sq ft (12.5 m ²)

STORAGE AND SHELF LIFE

- Product shelf life is 36 months when unopened and stored at room temperature.
- Store product in original container only.
- Close cap on container after each use.
- Use only when surface temperatures are between 50° F – 90° F (10° C – 32° C).

SAFETY

- KEEP OUT OF REACH OF CHILDREN.
- DO NOT SWALLOW. If swallowed, do not induce vomiting: seek immediate medical attention.
- AVOID CONTACT WITH EYES AND SKIN. Wear gloves and eye protection during application. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. If irritation continues, seek immediate medical attention.
- **Reference product MSDS for complete safety information.**

LIMITATION OF LIABILITY

Information on this technical data sheet is true and accurate at date of issuance, but subject to change without notice. Centura products conform to the highest quality standards but no other guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor, or other consequential damages is hereby excluded.

TECHNICAL SUPPORT

Web Site: www.nugrout.com

Email: technical@nugrout.com

Phone: 1.800.NUGROUT (1.800.684.7688)

Manufactured by: Centura Paint Manufacturing
4300 Northwest 1st Avenue
Boca Raton, Florida 33431
(561) 391-8797
Made in the U.S.A.